

Listing of Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A transmitter that uses a dual packet configuration for wireless communication, comprising:

a first modulator that modulates a first portion of each packet solely according to a serial modulation; and

a second modulator that modulates a second portion of each packet solely according to a parallel modulation;

the serial modulation comprising direct sequence spread spectrum (DSSS); and
the parallel modulation comprising orthogonal frequency division multiplexing (OFDM).

2. (Canceled)

3. (Previously Presented) The transmitter of claim 21, wherein the first portion includes a preamble and a header.

4. (Previously Presented) The transmitter of claim 3, wherein the preamble comprises a long preamble.

5. (Previously Presented) The transmitter of claim 3, wherein the preamble comprises a short preamble.

6. (Previously Presented) The transmitter of claim 3, the header including an OFDM mode bit.

7. (Previously Presented) The transmitter of claim 6, the header further including a length field indicating the duration the second portion.

8. (Currently Amended) The transmitter of claim ~~21~~, the second portion further comprising:

an OFDM synchronization pattern;

an OFDM signal symbol; ~~and~~

an OFDM payload[.];

the OFDM signal symbol including a data rate section and a data count section.

9. (Previously Presented) The transmitter of claim 8, further comprising:

the OFDM signal symbol including a data rate section and a data count section.

10. (Currently Amended) The transmitter of claim ~~21~~, further comprising:

the first portion based on a first clock fundamental; and

the second portion based on a second clock fundamental.

11. (Previously Presented) The transmitter of claim 10, wherein the first clock fundamental is approximately 22 Megahertz (MHz) and the second clock fundamental is approximately 20 MHz.

12. (Currently Amended) The transmitter of claim ~~21~~, wherein the first and second portions are based on a single clock fundamental.

13. (Previously Presented) The transmitter of claim 12, further comprising:

the second portion including OFDM symbols wherein each OFDM symbol includes a guard interval with a standard number of samples for OFDM.

14. (Previously Presented) The transmitter of claim 12, further comprising:
the second portion including OFDM symbols wherein each OFDM symbol
includes a guard interval with an increased number of samples.

15. (Previously Presented) The transmitter of claim 12, further comprising:
the second portion including OFDM symbols wherein each OFDM symbol
includes a reduced number of frequency subcarriers.

16. (Previously Presented) The transmitter of claim 15, wherein each OFDM
symbol includes 48 frequency subcarriers.

17. (Previously Presented) The transmitter of claim 15, wherein each of the
frequency subcarriers is a data subcarrier.

18. (Previously Presented) The transmitter of claim 15, wherein the frequency
subcarriers include at least one pilot tone.

19. (Previously Presented) The transmitter of claim 15, further comprising:
each of the frequency subcarriers initially comprising a data subcarrier; and
wherein a subset of the data subcarriers and replaces the discarded data
subcarriers with a corresponding number of pilot tones for transmission.

20. (Currently amended) A wireless communication device that is configured to
communicate using a dual packet configuration, comprising:

a transmitter configured to transmit packets with a dual configuration;

a receiver configured to receive packets with a dual configuration; and

the dual packet configuration including first and second portions, the first portion modulated solely according to a serial modulation method and the second portion modulated according to a parallel modulation method,

wherein the serial modulation is direct sequence spread spectrum (DSSS) and the parallel modulation method is orthogonal frequency division multiplexing (OFDM).

21. (Canceled)

22. (Currently Amended) The wireless communication device of claim ~~21~~20, the first portion including a header with an OFDM mode bit.

23. (Original) The wireless communication device of claim 22, the header further including a length field indicating the duration of the second portion.

24. (Currently Amended) The wireless communication device of claim ~~21~~20, further comprising:

a first clock source based on a first clock fundamental, the first portion based on the first clock fundamental; and

a second clock source based on a second clock fundamental, the second portion based on the second clock fundamental

25. (Original) The wireless communication device of claim 24, wherein the first clock fundamental is approximately 22 Megahertz (MHz) and the second clock fundamental is approximately 20 MHz.

26. (Currently Amended) The wireless communication device of claim ~~21~~20, further comprising:

a clock source based on a clock fundamental, the first and second portions based on the clock fundamental.

27. (Original) The wireless communication device of claim 26, wherein the second portion includes OFDM symbols, each OFDM symbol including a guard interval with a standard number of samples for OFDM.

28. (Original) The wireless communication device of claim 26, wherein the second portion includes OFDM symbols, each OFDM symbol including a guard interval with an increased number of samples.

29. (Original) The wireless communication device of claim 26, wherein the second portion includes OFDM symbols, each OFDM symbol including a reduced number of frequency subcarriers.

30. (Original) The wireless communication device of claim 29, wherein each of the frequency subcarriers is a data subcarrier.

31. (Original) The wireless communication device of claim 29, wherein the frequency subcarriers include at least one pilot tone.

32. (Original) The wireless communication device of claim 29, further comprising:

the transmitter discarding at least one of the data subcarriers and replacing the discarded data subcarriers with a corresponding number of pilot tones; and

the receiver regenerating the discarded data subcarriers based on received data subcarriers.

33. (Original) The wireless communication device of claim 20, further comprising:

the transmitter and receiver each capable of communicating in a super short mode in which only the second portion modulated according to the parallel modulation is utilized.

34. (Original) The wireless communication device of claim 20, further comprising:

the transmitter and receiver each capable of communicating in a standard mode in which the second portion is modulated according to the serial modulation.

35. (Original) The wireless communication device of claim 20, further comprising:

the transmitter and receiver each configured to operate in the 2.4 gigahertz frequency band.

36. (Currently Amended) A method of wireless communication using a dual packet configuration, comprising:

modulating a first portion of each packet solely according to a serial modulation; and

modulating a second portion of each packet according to a parallel modulation;

the modulating a first portion of each packet comprising modulating according to direct sequence spread spectrum (DSSS); and

the modulating a second portion of each packet comprising modulating according to orthogonal frequency division multiplexing (OFDM).

37. (Canceled)

38. (Currently Amended) The method of claim ~~37~~36, further comprising:
including a header with an OFDM mode bit in the first portion; and
including a length field in the header indicating a duration of the second portion.

39. (Currently Amended) The method of claim ~~37~~36, further comprising:
the modulating a first portion of each packet comprising modulating based on a first clock fundamental; and
the modulating a second portion of each packet comprising modulating based on a second clock fundamental.

40. (Currently Amended) The method of claim ~~37~~36, wherein the modulating first and second portions of each packet comprises modulating based on a single clock fundamental.

41. (Original) The method of claim 40, wherein the modulating the second portion of each packet comprises including a guard interval with a standard number of samples for each OFDM symbol.

42. (Original) The method of claim 40, wherein the modulating the second portion of each packet comprises including a guard interval with an increased number of samples for each OFDM symbol.

43. (Original) The method of claim 40, wherein the modulating the second portion of each packet comprises including a reduced number of frequency subcarriers for each OFDM symbol.

44. (Original) The method of claim 43, further comprising:
discarding a subset of the data subcarriers;
replacing the discarded data subcarriers with a corresponding number of pilot tones for transmission; and
regenerating the discarded data subcarriers based on received data.

45. (Original) The method of claim 36, further comprising:
switching to a super short mode of operation in which only the second portion modulated according to the parallel modulation is utilized for communications.

46. (Original) The method of claim 36, further comprising:
switching to a standard mode of operation in which the second portion is modulated according to the serial modulation.